

Hot Water Pressure Washers

HEO Series Diesel - Belt Drive - Stationary/Skid-Mount



HEO-3004-0E8G shown with optional 20-gallon fuel supply (HX-0218)



- ✓ Single or three-phase open drip-proof electric motor with thermal overload protection
- ✓ Belt drive triplex General pump with ceramic plunger
- ✓ Powder coated steel frame and removable side panels
- ✓ Adjustable high pressure detergent injection
- ✓ 10-inch draft diverter included
- ✓ Factory preset trapping unloader
- ✓ Thermal relief valve
- ✓ Pressure switch and over-pressure safety controls
- ✓ 24-volt control system
- ✓ Polyethylene float tank (4-gallon with in-line screen filter)
- ✓ ½-inch schedule 80-coil with 5 pancake heat exchanger
- ✓ Adjustable thermostat
- ✓ Quick connect nozzles (0°, 15°, 25° and 40°)
- ✓ 50-foot x ¾-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors
- ✓ Professional-grade insulated trigger gun with safety lock-off
- ✓ Adjustable pressure insulated dual lance with fixed detergent nozzle

Model No.	PSI	GPM	Horsepower/Motor	Ship Wt.	Net Wt.
HEO-2004-0E2G	2000	4.2	6.0 HP, 230V, 1Ø, 27.1A	844 lbs.	724 lbs.
HEO-2004-0E3G	2000	4.2	6.0 HP, 230V, 3Ø, 17.6A	844 lbs.	724 lbs.
HEO-2004-0E4G	2000	4.2	6.0 HP, 460V, 3Ø, 8.8A	844 lbs.	724 lbs.
HEO-2004-0E8G	2000	4.2	6.0 HP, 208V, 1Ø, 29.8A	844 lbs.	724 lbs.
HEO-2004-0E9G	2000	4.2	6.0 HP, 208V, 3Ø, 20.1A	844 lbs.	724 lbs.
HEO-3004-0E2G	3000	3.9	8.0 HP, 230V, 1Ø, 38.6A	878 lbs.	758 lbs.
HEO-3004-0E3G	3000	3.9	8.0 HP, 230V, 3Ø, 21.6A	878 lbs.	758 lbs.
HEO-3004-0E4G	3000	3.9	8.0 HP, 460V, 3Ø, 10.8A	878 lbs.	758 lbs.
HEO-3004-0E8G	3000	3.9	8.0 HP, 208V, 1Ø, 42.1A	878 lbs.	758 lbs.
HEO-3004-0E9G	3000	3.9	8.0 HP, 208V, 3Ø, 24.6A	878 lbs.	758 lbs.
HEO-3005-0E2G	3000	4.8	10.0 HP, 230V, 1Ø, 45.6A	878 lbs.	758 lbs.
HEO-3005-0E3G	3000	4.8	10.0 HP, 230V, 3Ø, 26.6A	878 lbs.	758 lbs.
HEO-3005-0E4G	3000	4.8	10.0 HP, 460V, 3Ø, 13.3A	878 lbs.	758 lbs.
HEO-3005-0E8G	3000	4.8	10.0 HP, 208V, 1Ø, 50.3A	878 lbs.	758 lbs.
HEO-3005-0E9G	3000	4.8	10.0 HP, 208V, 3Ø, 30.6A	878 lbs.	758 lbs.

OPTIONS

Part No.	Description	Fits Model(s)
HX-0104	K7 unloader (flow activated) (auto start/stop N/A) - Converts pressure trapping unloader system to flow actuated K7 unloader. Pressure is not trapping in the discharge line when trigger is released	HEO-3004 models
HX-0106	Hour meter - Displays number of hours unit has been in operation	All models
HX-0107*	Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	All models
HX-0108*	(1) Remote station (auto start/stop N/A) - Adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
HX-0110	Additional remotes (up to 3) - Additional remotes that may be added to unit after the first remote is installed	All models
HX-0111	Auto start/stop - When trigger gun is released timer will turn unit off, when trigger gun is pulled unit will restart	All models
HX-0112	K7 unloader (flow activated) (auto start/stop N/A) - Converts pressure trapping unloader system to flow actuated K7 unloader. Pressure is not trapping in the discharge line when trigger is released	2004 & 3005 models
HX-0114	Dual gun control - See HX-0113 for description	3005 models
HX-0115	Stainless-steel access panels - Converts powder coated painted access panels to stainless-steel material	All models
HX-0116	Stainless-steel coil wrap - Converts powder coated painted coil wrap to stainless-steel material	All models
HX-0117	Painted box kit - Adds painted side and end panels	All models
HX-0118	Painted and stainless-steel box kit - Adds stainless-steel side panels and painted end panels	All models
HX-0120	250°F steam upgrade - See HX-0119 for description	2004 models
HX-0121	250°F steam upgrade - See HX-0119 for description	3004 models
HX-0122	250°F steam upgrade - See HX-0119 for description	3005 models
HX-0124	Auto start/stop and first remote - When trigger gun is released timer will turn unit off, when trigger gun is pulled unit will restart; adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
HX-0216	Elevated float tank, 4.0 GPM - Float tank is located at the back of the unit	All models
HX-0217	Elevated float tank, 5.0 GPM - Float tank is located at the back of the unit	All models
HX-0218^	(2) 10-gallon fuel tanks - Adds 20-gallon fuel capacity to unit versus hose hook-up to fuel supply	All models
HX-0223*	Time delay shutdown and first remote box (kit option) - Timer will shut unit off automatically when trigger gun is released and timer reaches setting; Adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models

*Options HX-0107 & HX-0108 cannot be ordered together, you will need to order HX-0223 instead.

^You must also order option HX-0216 or HX-0217 when ordering HX-0218.



Hanson Industrial-Peoria Inc. - 611 McKinley Ave. Bartonville, IL 61607 - (309)697-3508