

HVS Series Gasoline/Diesel - Belt Drive - Stationary/Skid-Mount



HVS-3505-0H6G



Model No.	PSI	GPM	Horsepower/Displacement/Engine	Ship Wt.	Net Wt.
HVS-3005-0K6G	3000	4.8	624cc Kohler	819 lbs.	713 lbs.
HVS-3005-0V6G	3000	4.8	480cc Vanguard OHV	816 lbs.	710 lbs.
HVS-3006-0B7G [^]	3000	5.6	15.5 HP Kubota	940 lbs.	836 lbs.
HVS-3008-1H6G	3000	8.0	GX690 Honda OHV	854 lbs.	750 lbs.
HVS-3008-0K6G	3000	8.0	725cc Kohler	854 lbs.	750 lbs.
HVS-3504-0K6G	3500	3.8	624cc Kohler	814 lbs.	710 lbs.
HVS-3504-0V6G	3500	3.8	480cc Vanguard OHV	798 lbs.	704 lbs.
HVS-3505-0B7G [^]	3500	4.7	15.5 HP Kubota	940 lbs.	836 lbs.
HVS-3505-1H6G	3500	4.7	GX630 Honda OHV	854 lbs.	750 lbs.
HVS-3505-0K6G#	3500	4.7	624cc Kohler	854 lbs.	750 lbs.
HVS-3505-0V6G	3500	4.7	627cc Vanguard OHV	854 lbs.	750 lbs.
HVS-3506-1H6G	3500	5.6	GX630 Honda OHV	864 lbs.	760 lbs.
HVS-3506-0K6G	3500	5.6	725cc Kohler	864 lbs.	760 lbs.
HVS-4004-0K6A*#	4000	4.0	624cc Kohler	854 lbs.	750 lbs.
HVS-4004-1V6G*	4000	4.0	627cc Vanguard OHV	854 lbs.	750 lbs.
HVS-4005-0B7G [^]	4000	4.5	15.5 HP Kubota	940 lbs.	836 lbs.

[^]Diesel unit.

#Higher performance 624cc Kohler engine.

•Models equipped with trapping unloader, all other models equipped with K7 flow actuated unloader.

- ✓ Performance-proven Industrial gasoline or diesel engine with electric start (battery not included)
- ✓ Belt drive triplex piston General or AR pump with ceramic plungers
- ✓ 2900-watt generator
- ✓ Heavy-duty powder coated steel square tube frame
- ✓ High quality fuel filter/water separator ensures clean fuel supply
- ✓ Polyethylene burner and engine fuel tanks
- ✓ 80-mesh, high-volume, stainless-steel screen inlet water strainer
- ✓ Pressure relief valve protects against excessive system pressure
- ✓ Heavy-duty dual cogged belt drive system
- ✓ 10.0-gallon gas tank capacity
- ✓ 10.0-gallon burner tank fuel capacity with 3.37-gph burner fuel consumption (2.76-gph on HVS-3504-0V6G)
- ✓ No. 1 or No. 2 diesel or kerosene fired burner
- ✓ Quick connect nozzles (0°, 15°, 25° and 40°)
- ✓ 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors
- ✓ Professional-grade Insulated trigger gun with safety lock-off
- ✓ Adjustable pressure insulated dual lance with fixed detergent nozzle

OPTIONS

Part No.	Description	Fits Model(s)
HX-0130	Three-way ball valve - Allows pressure washer to be operated from garden hose/float tank or trailer supply tank by adjusting ball lever valve	All models
HX-0131	High pressure detergent injector (K7) - Supplies soap injection through the high pressure pump while spraying; pressure washers with K7 flow actuated unloaders only	3005, 3006, & 3500-PSI models
HX-0132	Steam combination 250°F (K7) - Increases outlet temperature to 250°F. Steam option for models equipped with K7 flow actuated unloaders.	HVS-3504 models
HX-0133	Steam combination 250°F (K7) - Increases outlet temperature to 250°F. Steam option for models equipped with K7 flow actuated unloaders.	HVS-3005 & HVS-3505 models
HX-0135	Steam combination 250°F (K7) - See HX-0132 for description	HVS-3506 models
HX-0136	Steam combination 250°F (K7) - See HX-0132 for description	HVS-3006-0B7G
HX-0137*	Steam combination 250°F (requires trapping unloader) - Increases outlet temperature to 250°F.	HVS-3504 models
HX-0138*	Steam combination 250°F (K7) - See HX-0137 for description	HVS-3005 models
HX-0139*	Steam combination 250°F (K7) - See HX-0137 for description	HVS-3505 models
HX-0140*	Steam combination 250°F (K7) - See HX-0137 for description	HVS-3506 models
HX-0141*	Steam combination 250°F (K7) - See HX-0137 for description	HVS-3006-0B7G
HX-0142*	Steam combination 250°F (K7) - See HX-0137 for description	4000-PSI models
HX-0143	Trapping unloader - For longer hose runs and cleaning elevated areas	HVS-3006 & HVS-3506 models
HX-0145	Adjustable temperature control - Operator is able to adjust outlet water temperature between 96°F-250°F	All models
HX-0146	Hour meter - Displays number of hours unit has been in operation	All models
HX-0147	Four point lifting capability - Allows unit to be lifted by crane	All models
HX-0148*	Detergent (requires trapping unloader) - Supplies soap injection through the high pressure pump while spraying; pressure washers with pressure trapping unloader only	HVS-3005 to HVS-3506 models
HX-0149*	Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	HVS-3006-0B7G & HVS-3506 models
HX-0198	Stainless-steel frame - Converts powder coated painted frame to stainless-steel material	All models
HX-0200	Trapping unloader - For longer hose runs and cleaning elevated areas	HVS-3005 & HVS-3505 models
HX-0201	Trapping unloader - For longer hose runs and cleaning elevated areas	HVS-3504 models
HX-0202	Dual gun - See HX-0149 for description	HVS-3008 models
HX-0203	Kohler engine upgrade - Higher performance 725cc Kohler engine	HVS-3008-0K6G

*To order these options you must also order HX-0143, HX-0200 or HX-0201 (N/A on 4000-PSI models which already come equipped with trapping unloader.)

ACCESSORIES

Part No.	Description	Fits Model(s)
20-1070A18	Removable painted front panel - Provides a protective panel and gives unit a more finished look	All models
50-0177	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	Gasket (for 50-0177) - Seals between 50-0177 stack adapter and boiler housing	All models
AW-5740-0000	Wheel kit - Allows unit to become portable	All models