

{Hand Carry/Portable}



Inverters

1700 - 3200 - 4300 Maximum Wattage

Get clean, quiet, high-power output with this portable inverter! A perfect fit for the recreational vehicle industry.



GEN-1700-iMSO



GEN-4300-iMSO

Additional Features:

- ✓ Low oil shutdown engine
- ✓ **Inverter technology** reduces size, weight, noise and fuel consumption
- ✓ **Inverter technology** produces commercial quality AC power for sensitive electronic equipment
- ✓ Idle control
- ✓ Special vibration control and low-tone mufflers further reduce noise
- ✓ Battery charging
- ✓ Fuel shutoff valve
- ✓ USDA/USFS-approved spark arrestors
- ✓ Circuit breaker protected
- ✓ Meets CARB and EPA emission standards

3200- & 4300-Watt Additional Features:

- ✓ Sound reducing materials are highly fire-resistant
- ✓ Roll cage design with four (4) wheels
- ✓ Fuel gauge
- ✓ Electric start (battery not included)
- ✓ Voltmeter/hour meter
- ✓ RV application advantage - will run an air conditioner unit (15,000-BTU), refrigerator and microwave (3200-watt model)*
- ✓ RV application advantage - will run an air conditioner unit (15,000-BTU), refrigerator and microwave plus interior lights (4300-watt model)*

**Based on tests conducted on a 2005 5th-wheel camper. Test results are available. Individual test results could vary depending on condition and efficiency of appliance.*

Unique soundproof panels reduce noise (1700 watt model)

Double-wall acoustical housing - damping panel and resin panel reduces both high and low frequency noise (3200- & 4300-watt models)

Easy-grip frame design maximizes ease of handling (1700 watt model)

Specifications:

Model #	GEN-1700-iMSO	GEN-3200-iMSO	GEN-4300-iMSO
Max. AC output	1,650 watts	3,200 watts	4,300 watts
Rated AC output	1,350 watts	2,800 watts	3,800 watts
HP/Displacement	2.8/86 cc	7.0/211 cc	9.0/265 cc
Engine	Subaru OHV	Subaru OHC	Subaru OHC
Frequency/Voltage	60Hz/120V	60Hz/120V	60Hz/120V
Max. amps (120V)	13.8	26.7	35.8
Cont. amps (120V)	11.2	23.3	31.7
Receptacles	120V, 20A GFCI duplex	120V, 20A GFCI duplex 120V, 30A twist lock	120V, 20A GFCI duplex 120V, 30A twist lock
Main circuit breaker	Electronic circuit protection	Electronic circuit protection	Electronic circuit protection
Rated speed	4,200 RPM	3,600 RPM	3,600 RPM
Decibel rating	59.0	58.0	62.0
Fuel capacity	1.1 gallon	3.7 gallon	4.2 gallon
Run time (at full load)	3.5 hours	5.5 hours	5.6 hours
Dim. (LxWxH)	19.3in.x11.6in.x17.5in.	21in.x18.9in.x22.9in.	22.8in.x20.7in.x24.3in.
Shipping weight	55 lbs.	143 lbs.	174 lbs.
Net weight	44.5 lbs.	131 lbs.	162 lbs.

Inverter generator ratings represent no-load sound levels. Rating represents minimum noise level rating.

Options:

32-0915 RV Generator Adapter - 30A/125V female/male; use to connect RV cordsets to 30A generators

Model #	32-0915
GEN-1700-iMSO	
GEN-3200-iMSO	●
GEN-4300-iMSO	●



GFCI 5-20R



L5-30R
125 VAC



611 Mc Kinley Ave.
Bartonville, IL 61607
888-345-0903