

Single- and Dual-Axle Trailers

Single- and Dual-Axle Trailers



AW-9000-0005 shown with optional HVS-3505-OMGH hot water pressure washer and optional hose reels



AW-9000-0003 shown with optional HVS-3505-OMGH hot water pressure washer and optional hose reels

Single Axle Trailer

- ✓ 5-foot x 8½-foot trailer
- ✓ 3-inch x 4¼-inch angle frame
- ✓ (1) 3,500 lb. axle
- ✓ (2) ST205-75R 15-inch radial tires with white spoke rims
- ✓ 2-inch coupler
- ✓ Swivel jack with pad
- ✓ 3,500 gross vehicle weight
- ✓ Tanks are enclosed in a powder coated steel frame

Dual Axle Trailer

- ✓ 5-foot x 8½-foot trailer
- ✓ 3-inch x 4¼-inch angle frame
- ✓ (2) 3,500 lb. axles with brakes on each side
- ✓ (2) ST205-75R 15-inch radial tires with 6-bolt white spoke rims
- ✓ 2½-inch coupler with 14,000 lb. capacity
- ✓ Swivel jack with pad
- ✓ 7,000 gross vehicle weight
- ✓ Tanks are enclosed in a powder coated steel frame
- ✓ 5-foot x 4-foot x 12-inch storage area located under water tanks, access doors located at back of trailer

High Pressure Hose Reel Options

- ✓ These high pressure hose reel options are available for both single and dual-axle trailers. They include the hose reel with mounting bracket and jumper hose.

Low Pressure Hose Reel Option

- ✓ This low pressure hose reel option is available for both single and dual-axle trailers. It includes the hose reel with mounting bracket and plumbing.

Back-Flow Preventors

- ✓ Back-flow preventors are required on trailer units in some states. These are mounted on the inlet side of the trailer and have several options for them to be mounted on trailers.

Part No.	Description
AW-9000-0005	Single-axle trailer with 200-gallon water tank and surge brakes
AW-9000-0006	Single-axle trailer with 200-gallon water tank and electric brakes
AW-9000-0007	Single-axle trailer with 200-gallon water tank only without brakes
AW-9000-0003	Dual-axle trailer with (2) 200-gallon water tanks and surge brakes
AW-9000-0004	Dual-axle trailer with (2) 200-gallon water tanks and electric brakes

OPTIONS

TX-0001	High pressure hose reel - 13-inch
TX-0002	High pressure hose reel - 16-inch
TX-0003	Low pressure hose reel - 16-inch
	<i>*Note: 22-0136 back-flow preventor must be used with TX-0003, when used in California.</i>
TX-0004	Trailer tank bypass - Used on dual-axle trailers, removes float system, chemical injector and 3-way ball valve while adding the necessary plumbing, for use with HDS & HDC Series pressure washers
TX-0005	Trailer tank bypass - Used on dual-axle trailers, removes float system while adding the necessary plumbing, for use with HVS Series pressure washers
TX-0006	Trailer tank bypass - Used on single-axle trailers, removes float system, chemical injector and 3-way ball valve while adding the necessary plumbing, for use with HDS & HDC Series pressure washers
TX-0007	Trailer tank bypass - Used on single-axle trailers, removes float system while adding the necessary plumbing, for use with HVS Series pressure washers

PARTS & ACCESSORIES

15-0159	Jumper hose
13-0179A01	Mounting bracket
22-0136	Back-flow preventor - Use if a trailer has a hose reel for the supply
50-0136	Hose reel - 13-inch, 100-foot maximum hose length
50-0137	Hose reel - 16-inch, 200-foot maximum hose length



Hanson
Industrial - Peoria, Inc.