

# AIR COMPRESSORS 20-Gallon



PORTABLE - ELECTRIC/  
GASOLINE - SINGLE STAGE



AC1-PE15-20M

## FEATURED ON ALL MODELS

**Compressor Pump:** Splash lubricated cast iron crankcase · Aluminum head for heat dissipation · Stainless-steel braided discharge hose · Large canister intake filter

**Frame:** Powder coated ASME coded 20-gallon receiver tank · 7-gauge base plate to reduce vibration · Convenient lifting handle · Two pneumatic tires with tubes and steel hubs

**Components:** Belt tightening system pulls engine straight to ensure constant belt alignment · Manual drain valves for proper maintenance

## ELECTRIC MODELS

**Motor:** Industrial UL-listed electric motor · Auto start/stop (continuous run optional) · Thermal overload motor protection

**Components:** Industrial grade pressure switch · 10-inch fly wheel for extra cooling and longer life

## GASOLINE MODELS

**Engine:** Industrial Honda OHV or Subaru OHC engine · Pneumatic idle control to conserve fuel

**Components:** 12-inch fly wheel for extra cooling and longer life · Quality pilot valve unloader

If storage capacity is what you need, then look no further. This single-stage model is portable and allows for a whopping 20-gallons of air storage capacity! The electric model is the perfect solution for service shops.



Quality cast iron single stage compressor



Regulator and two gauges for tank and outlet pressure



14-gauge powder coated two-piece belt guard with 1/4-turn release for quick access to belts

Model No.	CFM @ 100 PSI	HP/Motor	Pump	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AC1-PE15-20M	6.5	1.5/120V, 13.2A Electric	Cast iron	NEMA 5-15P	37in.x32.5in.x32in.	265 lbs.	169 lbs.
AC1-PE02-20M	8.4	2.0/120V, 18.8A Electric	Cast iron	NEMA 5-20P	37in.x32.5in.x32in.	260 lbs.	198 lbs.

Model No.	CFM @ 100 PSI	Displacement/Engine	Pump	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM1-PH65-20M	13.1	196cc Honda OHV	Cast iron	44.5in.x23.5in.x33in.	272 lbs.	212 lbs.
AM1-PR07-20M	13.1	211cc Subaru OHC	Cast iron	44.5in.x23.5in.x33.5in.	272 lbs.	212 lbs.

### Options

70-0357, 70-0380	Engine oil drain	AX-0008	Dual control
AX-0002	Auto drain plastic bowl	Consult factory	Cable throttle control
AX-0004	Manual drain plastic bowl	TX-1002-W	Puncture-proof tires



NEMA 5-15P,  
15-amp plug



NEMA 5-20P,  
20-amp plug