

## JP Series Electric - Direct Drive - Powder Coated Steel Frame



JP-2003-1ME1



Certified in USA & Canada:  
JP-1002 & JP-1502 single  
phase models



Certified in USA only:  
JP-2003, JP-2503 &  
JP-3004 models

- ✓ Totally enclosed fan-cooled electric motor
- ✓ Direct drive triplex piston General or AR pump with ceramic plungers
- ✓ Powder coated steel base plate
- ✓ 1-inch powder coated steel tube handles

| Model No.         | PSI  | GPM | Horsepower/Motor                                      | Ship Wt. | Net Wt.  |
|-------------------|------|-----|---|----------|----------|
| JP-1002-0ME1**^#  | 1000 | 2.0 | 1.5 HP, 120V, 1Ø, 15.0A                               | 120 lbs. | 90 lbs.  |
| JP-1002-2ME1**^#+ | 1000 | 2.0 | 1.5 HP, 120V, 1Ø, 15.0A                               | 120 lbs. | 90 lbs.  |
| JP-1502-0ME1**^#  | 1500 | 2.0 | 2.0 HP, 120V, 1Ø, 20.0A                               | 120 lbs. | 90 lbs.  |
| JP-1502-2ME1**^#+ | 1500 | 2.0 | 2.0 HP, 120V, 1Ø, 20.0A                               | 120 lbs. | 90 lbs.  |
| JP-2003-1ME1**^#  | 2000 | 2.8 | 4.0 HP, 230V, 1Ø, 16.0A                               | 162 lbs. | 112 lbs. |
| JP-2503-1ME1**^#  | 2500 | 3.2 | 6.0 HP, 230V, 1Ø, 24.1A                               | 275 lbs. | 225 lbs. |
| JP-2503-0ME3      | 2500 | 3.2 | 6.0 HP, 230V, 3Ø, 15.0A or<br>6.0 HP, 460V, 3Ø, 7.5A  | 275 lbs. | 225 lbs. |
| JP-3004-1ME1^     | 3000 | 3.9 | 8.0 HP, 230V, 1Ø, 34.5A                               | 275 lbs. | 225 lbs. |
| JP-3004-0ME3      | 3000 | 3.9 | 8.0 HP, 230V, 3Ø, 20.0A or<br>8.0 HP, 460V, 3Ø, 10.0A | 275 lbs. | 225 lbs. |

\*35-foot cord with ground fault circuit interrupter (GFCI).

^Single phase models are CSA certified.

#Models equipped with General pumps, all other models equipped with AR pumps.

+Pump accepts incoming water up to 180°F.

### OPTIONS

| Part No.  | Description   | Fits Model(s)        |
|-----------|---|----------------------|
| CX-0005   | Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips | All models           |
| CX-0066   | 460V on 6.0-HP, 3-phase models - For when you have 460V of power available  | JP-2503-0ME3         |
| CX-0067   | 460V on 8.0-HP, 3-phase models - For when you have 460V of power available  | JP-3004-0ME3         |
| TX-1002-W | Puncture-proof tires - Tires are flat-free and maintenance-free, 10-inch, white hub, two tires  | 1000-2000 PSI models |
| TX-1302-W | Puncture-proof tires - Tires are flat-free and maintenance-free, 13-inch, white hub, two tires  | 2500-3500 PSI models |

### ACCESSORIES

| Part No. | Description  | Fits Model(s) |
|----------|--|---------------|
| 50-0161  | High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up | All models    |