

Our portable kerosene-fired forced air space heaters provide powerful instant heat that is safe and economical.

# Kerosene Forced Air

HAND CARRY/PORTABLE - KEROSENE



MH-0215-0M10



Hand Carry  
MH-0070-0M10

Heavy-duty, high quality cast aluminum enclosed electric motor



Built-in temperature control thermostat with control dial (Digital temperature read out on 125 to 215,000 BTU models)



**Factory tested for multiple fuels: Kerosene, JP8/Jet A fuel, No. 1 and No. 2 fuel oil and No. 1 and No. 2 diesel fuel**

### FEATURED ON ALL MODELS

- Frame:** Rugged steel body · Extension cord wrap · Powder coated hood and gas tank
- Burner Head:** Clamped hoses · Secured photo cell · 1-piece cast aluminum · Secured fully insulated ignition connection
- Components:** High performance fan · Power switch · Secured internal components · Integral overheat and flame-out safety · Fuel gauge · Integrated air pressure gauge (not available on MH-0400 model) · Oversized fuel cap · High limit temperature shut-off · Sure start ignition for cold temperature starts · Dual connector ignitor

### MH-0125, MH-0175, MH-0215 & MH-0400 MODELS

- Frame:** Powder coated steel handles for easy lifting · 10-inch pneumatic wheels (13-inch wheels on MH-0400 model) · Spare parts storage system (located on back of unit) · Fuel drain plug
- Components:** Error indicator read-out

**For use in workshops, garages, construction sites and farms.**



**Important Notes**

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Must be plugged into an approved standard electrical outlet for operation

Model No.	MH-0070-0M10	MH-0125-0M10	MH-0175-0M10	MH-0215-0M10	MH-0400-0M10
Heat Output	70,000 BTU	125,000 BTU	175,000 BTU	215,000 BTU	400,000 BTU
Hot-Air Flow (CFM)	240	540	630	670	1,400
Air Pump Pressure (PSI)	4.0	5.0	7.5	9.0	8.5
AC Power	120 Volt/60Hz/1.5 Amp	120 Volt/60Hz/2.3 Amp	120 Volt/60Hz/2.7 Amp	120 Volt/60Hz/2.8 Amp	120 Volt/60Hz/2.8 Amp
Motor Size	1/8 HP	1/5 HP	1/4 HP	1/3 HP	1/2 HP
Fuel Tank Capacity	5.0 gal.	10.0 gal.	13.0 gal.	13.0 gal.	24.0 gal.
Fuel Consumption	.53 gal./hr.	.95 gal./hr.	1.34 gal./hr.	1.63 gal./hr.	3.05 gal./hr.
Max. Operating Hours	9.0	10.0	9.5	8.0	8.0
Heating Area	1,700 sq. ft.	3,100 sq. ft.	4,300 sq. ft.	5,300 sq. ft.	10,000 sq. ft.
Multi-Fuel Capable	Yes	Yes	Yes	Yes	Yes
Dimensions (LxWxH)	30in.x12in.x15in.	39in.x23in.x26in.	43in.x24in.x26in.	43in.x24in.x26in.	58in.x30in.x25in.
Ship Wt.	33 lbs.	60 lbs.	68 lbs.	71 lbs.	152 lbs.
Net Wt.	28 lbs.	54 lbs.	61 lbs.	64 lbs.	143 lbs.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations, and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information.