

For convenient, versatile radiant heat, these propane tank top heaters are great for outdoor use. Just connect to a standard 20 pound propane cylinder for up to 48 hours of heating.

Propane Radiant

PORTABLE - TANK TOP HEATING


Safety shut-off valve



High efficiency heat reflector



Heat regulator knob



MH-0015-IM10

MH-0030-IM10

*Propane tank not included

1
YEAR
LIMITED
WARRANTY

Important Notes

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation

FEATURED ON ALL MODELS

Frame: Heavy-duty construction · Cast aluminum manifold · Rust-proof chrome emitter guard · Rear burner safety guard · Swivel burner head (MH-0030 only)

Heat Output: Variable heat control valve · Clean, quiet, instant radiant heat

Components: Hand wheel connection for valve · Standard propane tank connection

For use in open workshops, construction sites, farms and for any other outdoor heating need.

Model No.	MH-0015-IM10	MH-0030-IM10
Heat Output (Single Burner)*	L-9,000 / M-12,000 / H-15,000 BTU	L-9,000 / M-12,000 / H-15,000 BTU
Heat Output (Double Burner)*	N/A	L-18,000 / M-24,000 / H-30,000 BTU
Ignition Type	Match light	Match light
Heat Settings	3	6
Propane Cylinder Size	20 lbs.	20 lbs.
Max. Operating Hours (20 lb. Cyl.)	L-48 / M-36 / H-28	L-48 / M-18 / H-14
Dimensions (LxWxH)	8.5in.x6.5in.x12.5in.	17.5in.x6.5in.x18in.
Ship Wt.	4 lbs.	8 lbs.
Net Wt.	3 lbs.	7 lbs.

*Heat output and operating hours are at Low, Medium and High Settings.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations, and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.